







Opportunities and Complexity In Reducing Mobile AC GHG Emissions

Stephen O. Andersen & Kristen Taddonio
US EPA
Ward Atkinson
Society of Automotive Engineers
Elvis Hoffpauir
Mobile Air Conditioning Society

Imagine Affordable Climate Protection

A global team of industry, government, and public authorities working together to investigate and commercialize new mobile AC technology that helps protect the climate while rewarding vehicle manufacturers, suppliers, service organizations, and owners.

CARB!

lank you

if putting the environment in the driver's seat!

AC Delco ACC Climate Control AGRAMKOW Airsept. Alliance of Automobile Manufacturers sociation of international

utomobile Manufacturers

Aux ration Department of Environment an. Heritage Austr Ian Federated Chamber of Auto otive industries Austral in Federation of Automotive

Parts N enufacturers Australia. Pluorocarbo Fluorocarbon Council reenhouse Office Australian Automotive Artermarket Industry Association

Bergstrom BMW

California Air Resources Board

CalsonicKansel Centro Ricerche Flat Clore Automotive DalmlerChrysler Delphi Corporation DENSO **DuPont Fluoroproducts**

Eccle des Mines de Paris Edith Cowan University (Australia) Environment Canada European Commission Flat Auto

Four Seasons Friends of the Earth

Honda Honeywell Hutchinson FTS Hyundai Indian institute of Technology Delhi Indian Ministry of Environment and Forests.

INEOS Fluor Institute of Governance and Sustainable Development International Organization of Standardization

Japan Automobile Manufacturers Association

Japan Fluorocarbon Manufacturers Association

Japan Industrial Conference for Ozone Layer and Climate Protection Japan Ministry of Economy, Trade

and industry Japan Ministry of Environment Johnson Confrols

Korea Advanced Institute of Science and Technology

Mattow

Mitsubishi Motors

Mobile Air Conditioning Partners

Mobile Air Conditioning Society Worldwide

Natural Resources Defense Council Nautronics

PPG Industries PSA Paugeot/Citroan Red Dot Refrider Refrigerant Redaim Australia RTI Technologias

Shecco

Sinochem USA

Skye International Holdings Snap-On Diagnostics

Society of Automotive Engineers Society of Indian Automobile

Manufacturers. Solvay Fluorochemicals

SPX Floblinair Subaru Subros.

Sun Test Suzuki

TATA Motors TEXA, S.p.a.

Texas Instruments

The Energy and Resources Institute

(India) TI Automotive Toyota.

Tracer Products

Transpro

TYC Genera Underwriters Laboratories United Nations Environment

Programme DTIE U.S. Army RDE Command

U.S. Army HDE Command
U.S. Department of Energy's National
Penewable Energy Laboratory
U.S. Environmental Protection Agency
University of Braunschweig (Germany)
University of Maryland
Uview Ultraviolet Systems
Valeo

Valido
Vehide Airconditioning Spedalists of
Australia

Australia
Visiteori Corporation
Volkswagen
Volvo Car Corporation
World Resources Instit
ZEXEL-Valeo

Congratulations to the Mobile Air Conditioning Climate Protection Partners for helping us all save money and drive a little cleaner. This global team of corporate, government, and environmental leaders is working together to rapidly improve the efficiency of your vehicle air conditioning systems by at least 30% and reduce refrigerant leakage by at least 50%. Vehicle manufacturers and suppliers are improving existing air conditioning systems and technicians are offering environmentally superior service as the global search for better refrigerants continues. These voluntary actions will ultimately avoid millions of tons of greenhouse gas emissions each year.

Visit our website at www.epa.gow/cppd/mac and help put the environment in the driver's seat.



Appreciate The Global Consensus


- An investment of less than \$50 per new vehicle can improve the energy efficiency of AC systems by at least 30% and reduce refrigerant leakage by at least 50%--with payback from fuel savings within two years and savings every year there after.
- Professional system repair using the latest service equipment can further reduce emissions
- New refrigerants can transform markets

Performance not Prescription

- Conspicuous Regulatory Neglect
 - Energy use not yet in US EPA fuel economy label or CAFE;
 ignored in national standards worldwide!
- The EC ban on HFC Refrigerants does not guarantee reductions in GHGs if fuel use is increased
- CARB performance standards can motivate the choice of best technology and guarantee GHG reductions while saving car owners money and stimulating employment in the vehicle service sector

U.S. Fuel Savings Taking into Account New Technology Penetration

- Assumptions
 - 30% reduction in AC power
 - Power reductions begin in 2010
 - Fleet grows through time (DOE's Vision model)
 - 234 million in 2010
 - 293 million in 2050
 - Fleet turnover in 16 years
 - VMT increases over time
 - 13,500 miles in 2010
 - 19,950 miles in 2050



Reduction in Refrigerant GHG Emissions Nearly Doubles the Climate Benefit

MAC Climate Protection Partnership

- Product Testing
- Labeling of Superior Products
- Incentives for Proper Service
- Rewards for Improving New Car MAC System Energy Efficiency and Refrigerant Containment



Certified A/C
Containment

First Things First @ CARB

- Take Full Advantage of CARB Membership in MAC Partnership
- Endorse SAE MAC Global Standards
 - Testing, Performance, & Service Standards
- Consider Incentives for New Service Equipment & Enhanced Service Procedures
- Reward Verified Energy Efficiency
- Avoid Snake Oil and...
 - ...Other Claims Too Good To Be True

More MAC Information

- I-MAC 30/50
 - www.epa.gov/cppd/mac; www.sae.org/news/releases/mobileac.htm
- SAE Alternate Refrigerant Symposium: 26-28 June 2006
 - www.sae.org/events/aars/; www.sae.org/ac
- VDA Winter Meetings
 - www.vda-wintermeeting.de
- MAC Summit Proceedings
 - 2003: www.europa.eu.int/comm/environment/air/mac2003/index.htm
 - 2004: www.epa.gov/cppd/2004macsummit.pdf
 - 2005: www.arb.ca.gov/research/macs2005/macs2005.htm
 - 2006: www.mac-summit.com/presentations
- California Climate Protection and MACS
 - http://www.arb.ca.gov/cc/ccms/ccms.htm
 - http://www.climatechange.ca.gov/climate_action_team/reports/index.html#supporting
- U.S. EPA MAC Partnership
 - www.epa.gov/cppd/mac





International Symposium on Near-Term Solutions for Climate Change Mitigation in California

Ward Atkinson
March 5-7, 2007



Search For The Mobile A/C Refrigerant That Is The Best For The Environment

- Must consider:
 - Direct emissions from refrigerant
 - Potential release to atmosphere over vehicle lifetime
 - Indirect emissions
 - System total weight [carried on vehicle all year]
 - System operating efficiency [fuel use] in the warm climate in California
 - Risks to Consumer and technician safety
 - Proven Long term system reliability
 - Costs vs the Benefits
 - Initial cost of the vehicle
 - Costs for Service over lifetime




Search For The Mobile A/C Refrigerant That Is The Best For The Environment

- Known Facts:
 - Current industry targets for new refrigerants is to provide:
 - Comparable system cooling performance to HFC-134a systems
 - Reduced refrigerant requirements over the system's lifetime [Reduce initial charge and leakage]
 - Reduced energy consumption [Improved fuel use]
- Compare all A/C systems/refrigerants for total Environmental impact using LCCP standards [Life Cycle Climate] Performance]



Life cycle analysis





Search For The Mobile A/C Refrigerant That Is The Best For The Environment

- SAE I-MAC Achieved Success in Meeting HFC-134a Goals
 - Reduced System Refrigerant Emissions by 50%
 - Improved System Energy Efficiency by 30%
 - Reduced in Vehicle Solar & High Ambient
 Temperature Heat Loads by 30%
 - Reduced Refrigerant Losses During Service by 50%



Developed a Standard to Estimate HFC-134a
 Annual Mobile Air Conditioning System
 Refrigerant Emissions





System Leakage



- Compressor Technology
 - Shaft Seal
 - Housing seals


Hose Technology

Fitting Connection Technology



3 Types of Hose Construction

Ultra-low Perm Barrier or Veneer Hose



Standard Barrier or Veneer Hose

All Rubber Hose





Metal Gasket °

Lowest Leakage

- Seal Washer with O-ring
- Seal Washer
- Multiple O-ring
- Single Captured O-ring
- Single O-ring







I-MAC Efficiency



Achieved the 30% goal by:

- Improved heat exchanger technology
 - Condenser
 - Evaporator
- Improved compressor technology
- Improved refrigerant control technology




New HFC-134a Systems For Marketplace

- Improved HFC-134a systems
 - Have less refrigerant leakage
 - Use less refrigerant
 - Are more efficient
- Reduced Service refrigerant loss Requires
 - New service equipment
 - Improved technician training
- Added costs can be rewarded using emission credits

J2727 HFC-134a Mobile Air Conditioning **Estimated System Refrigerant Emission Charts**


Production System

GM 9.7 grams/yr



Production System

10.9 grams/yr





Production System

% System Component Contribution

Toyota 22.3 grams/yr

- Production System
 - DCX van 25.4 grams/yr







New Refrigerants

- European phase-out of HFC-134a in 2011/2017
 - Alternatives:
 - R744 Carbon Dioxide Systems
 - Higher Cost
 - Less efficient in Warm Climates
 - May not be a global refrigerant
 - R152a
 - Need mitigation due to flammability
 - Secondary loop may be an option
 - New alternative refrigerants are being evaluated by:
 - SAE CRP-150
 - VDA Vehicle test program
 - JAMA Program
 - Rest of World may still use HFC-134a
 - Industry Wants a Single Low GWP Global Refrigerant



New Systems For Marketplace R-744 Carbon Dioxide

- R744 Systems Carbon dioxide
 - Initial use in Europe [Limited to other markets?]
 - If sold in USA meet SNAP requirements
- Requires
 - New service equipment
 - Under current federal regulations cannot be vented at service
 - High pressure system
 - Requires "Certified Technicians"
- Production systems may not be as efficient as prototype systems
 - [Less efficient than optimized development systems]
- Long term reliability not fully proven



New Systems For Marketplace HFC-152a

- ♦ HFC-152a (Secondary loop)
 - Improved performance over
 HFC-134a -- Including Idle Stop
 - -Single component chemical
 - Must be recovered at service
 - Requires
 - New service equipment
 - Improved technician training due to flammability



Search For A New Global Refrigerant

- Needs to be
 - Energy efficient
 - Comparable Performance to HFC-134a
 - Safe and not harmful to the environment or the consumer
 - Cost effective
 - New service equipment



New Refrigerants

- Current Industry activity --- Low GWP Refrigerants
- New candidates
- -- Low GWP Blend Refrigerants **Industry will select from** candidates:
 - Arkema
 - Dupont DP1
 - Honeywell Fluid H

 - Sinochem
 - Solvay

- New Refrigerant Are **Blends**
 - azeotropes/zeotropes
 - Some blend compositions remain the same (won't separate)
 - Some blend compositions can separate, change over vehicle life
- Ineous Fluor Auto AC-1 ◆ Not a single chemical like HFC-134a/HFC-152a



New Blend Refrigerants

- In general have less performance than HFC-134a
 - Require new system component development
 - Potential For Improvement
 - Heat exchangers
 - Compressors
- Require complete analysis for
 - Health and safety
 - Environmental impact
 - Meeting governmental requirements
 - SNAP ---- TSCA
- Must meet system material compatibility
 - Hoses --- seals
- Have temperature/pressure relationship similar to HFC-134a




New Blend Refrigerants

- Recovery
 - None can be Vented at service or end of vehicle life
- On site Recycling Currently unknown
 - Might require re-formulation before re-use
 - Might require recovery and return to supplier
- Requires unique tools and service equipment



Survey Year

Independent Service Facility A/C System Service Profiles



1990 — 2003



International Symposium on Near-Term Solutions for Climate Change Mitigation in California

March 5-7, 2007 Elvis Hoffpauir

Immediate Impact on Greenhouse Gas

- Incentives
 - Superior leak detection & recovery/charging equipment
- Regulations
 - Require return of refrigerant containers for refrigerant heel and container recovery

Society of Automotive Engineers Cooperative Research Program

Reduce Service Emissions by 50%



Identify, quantify and propose remedies for refrigerant losses at service, vehicle end of life

Quantify and address losses from one-way refrigerant containers

Evaluate and recommend improvements for service tools, equipment (new or revised standards) and service procedures

Produce educational programs and conduct outreach to reduce refrigerant emissions

I-MAC Service Team



- Refrigerant measurement
 - Recovery/charging
- Leak detection
- Field coupled hoses
- Container emissions (heel)
- Communication to vehicle salvage industry

Service Problems Identified: Leaks & Refrigerant Recovery




- 20 to 30% of refrigerant is not recovered at service & EOL
- Significant GHG Emissions
- Overcharged systems increasing fuel use, damaging components & possible pressure relief venting

Solution: New Refrigerant Recovery Equipment



Old J2210
70%
Refrigerant
recovered
at service
and EOL



New J2788 95% Refrigerant recovered *Drivers:*

- SAE
- EPA & CARB Regulations
- MACS and industry

Solution: Superior Leak Detectors



- **J1627**
 - Required only 1 range scale
 - Identified 0.5 ounce/year with probe 1/4 inch from leak
- **J2791**
 - New test procedure for certificatio
 - Requires at least 3 selectable ranges
 - Identifies 0.15 ounce/year with
 probe 3/8 inch from leak

Field Coupled Hose Assemblies



- As much as 50% of replacement A/C hoses are field coupled
- As much as 15% of field coupled hoses are defective
- Extreme inconsistency in sizing and materials selection of field coupling hose assemblies
- Wide variation in crimping styles, techniques and dimensional integrity

Solution: Shops Compliance with SAE J2064



- Factory certified assemblies or certified field hose coupling with proper equipment
- Standardized components and proper component matching
- Audited shop testing standards

HFC-134a Vehicle System and Service Technician Certification

- Programs identifying:
 - ◆ New HFC-134a systems
 - Reduced leaks
 - Improved efficiency
- I-MAC Facility and Technician Certification Programs



Vehicle End of Life



Continuing cooperation with the Automotive Recyclers Association (ARA) & the Institute of Scrap Recycling Industries (ISRI)

Proposed Blend Refrigerants

- Proposed blend refrigerants will have a major impact on service
- Each new refrigerant would require unique training, tools, and service equipment

Can CARB Find the Way?

- Require reduced leakage, energyefficient systems in new cars
- Encourage certified, professional training
 & the use of improved tools and equipment
- Require return of refrigerant containers for refrigerant heel recovery and container salvage (30 Lb. containers)